

DESCRIPTION

❖ CHARACTERS

- ❖ P3, outdoor full color screen, is a high-performance module specially developed by our company for outdoor. PCB adopts FR-4 double-layer circuit board design, plate thickness 1.2mm, surface treatment process is OSP, 84 driver ics, 16 pipe ics, HUB75 interface LED lamp using 1515 outdoor LED lamp beads, colloid color: frosted mist, luminous color: full color, visual Angle: 120 degrees

❖

❖ APPLICATION AREA







- ❖ Video advertising display
- ❖ Mall, large advertising display
- ❖ High-grade LED advertising, display card
- ❖ High-end supermarket display shelves, traffic light layout

SUMMARY


- ❖ Operating voltage 4.5~5V DC
- ❖ Maximum current 6.3A
- ❖ Maximum power 33.5W
- ❖ Gray level ≥ 13 bit
- ❖ Frame change frequency 50&60Hz
- ❖ Refresh frequency 3840Hz

CERTIFICATION

The certification types will be increased as needed. You can contact our company's salesperson to learn more.



For reflow soldering



ITEM		MODEL
		EL-OUT-ET-P3
Physical parameter	LED package	SMD1515-1R1G1B
	Horizontal view/vertical view	≤110/110
	Flatness	≥97%
	Bottom shell screw aperture	M4
	Input signal interface definition	HUB75
	Power socket specification	4P/90°
	Module weight KG/PCS	
	Class of protection	IP6X
Optical parameter	Luminous intensity Lm	4700-5000
	Gray level bit	≥13
	Temperature K	10500
	Contrast	≤4000:1
	Brightness control	Manual/automatic/program control
Electrical parameter	Operating voltage (DC) V	4.5~5V
	Maximum current A	6.3
	Peak power W/PCS	33.5
	Average power W/PCS	31.5
Performance parameter	Refresh frequency HZ	≥3840Hz
	Frame change frequency Frame	60
	Driving mode	Constant current drive
	Scanning mode	1/13
	Color correction	It is equipped with point by point correction of brightness and chroma
	Whole screen out of control point	≤0.003%, 出厂时为 0
	Regional runaway point	≤0.009%
	Screen temperature rise (using running state)	≤5°
Adaptation scenario	Operating ambient temperature	-10℃ ~ 60℃
	Operating environment humidity	35% ~ 75%RH, Non-condensing
	Usage scenario	Outdoor
Adaptive chassis	Product chassis dimensions (W x H)	640*480mm
	Chassis resolution (W x H)	208*156
	Input signal interface	RJ45
	Power signal interface	3* U-shaped terminals

描述		
	Class of protection	IP6X
White balance debugging parameters	R Brightness CD/M ²	3100
	R current A	2.28
	R-resistance KΩ	2D4
	G Brightness CD/M ²	6500
	G Electric current A	2.05
	G Resistance value KΩ	2D7
	B Luminance CD/M ²	6700
	B Electric current A	2.26
	B Resistance value KΩ	2D7
	W Luminance CD/M ²	4700-5000
	W Electric current A	6.3

特征

P3, 室外全彩屏, 是我司专门为户外研发的一款高性能模组, PCB 采用FR-4双层电路板设计, 板材厚度1.2mm, 表面处理工艺为 OSP, 驱动IC为84颗, 行管IC为16颗, HUB75接口 LED灯采用1515户外LED灯珠, 胶体颜色为: 磨砂雾状, 发光颜色: 全彩, 视觉角度: 120度

应用领域






- ❖ 视频广告展示
- ❖ 商场、中大型广告展示
- ❖ 高档LED广告、展示牌

概要


- ❖ 工作电压 4.5~5V直流
- ❖ 最大电流 6.3A
- ❖ 最大功率 33.5W
- ❖ 灰度等级 $\geq 13\text{bit}$
- ❖ 换帧频率 50&60Hz
- ❖ 刷新频率 3840Hz

认证

认证种类将会增加, 请联系本公司业务。



For reflow soldering



说明		型号
		EL-OUT-ET-P3
物理参数	LED 封装	SMD1515-1R1G1B
	水平视角/垂直视角	≤110/110
	平整度	≥97%
	底壳螺丝孔径	M4
	输入信号接口定义	HUB75
	电源座规格	4P/90°
	模组重量 KG/PCS	
	防护等级	IP6X
光学参数	发光强度 Lm	4700-5000
	灰度 bit	≥13
	色温 K	10500
	对比度	≤4000:1
	亮度调节	手动/自动/程控
电性参数	工作电压 (DC) V	4.5V~5V
	最大电流 A	6.3
	峰值功率 W/PCS	33.5
	平均功率 W/PCS	31.5
性能参数	刷新频率 HZ	≥3840Hz
	换帧频率 帧	60
	驱动方式	恒流驱动
	扫描方式	1/13
	色彩校正	配备亮度与色度逐点校正
	整屏失控点	≤0.003%，出厂时为 0
	区域失控点	≤0.009%
	屏幕温升（使用运行状态）	≤5度
适配场景	运行环境温度	-10℃~60℃
	运行环境湿度	35%~75%RH，无凝结
	使用场景	室外
	产品机箱尺寸(宽×高)	640*480mm

适配机箱	机箱分辨率(宽×高)	208*156
	输入信号接口	RJ45
	电源信号接口	3*U 形端子
	防护等级	IP6X
白平衡调试参数	R 亮度 CD/M ²	3100
	R 电流 A	2.28
	R 阻值 K Ω	2D4
	G 亮度 CD/M ²	6500
	G 电流 A	2.05
	G 阻值 K Ω	2D7
	B 亮度 CD/M ²	6700
	B 电流 A	2.26
	B 阻值 K Ω	2D7
	W 亮度 CD/M ²	4700-5000
	W 电流 A	6.3